

E-Z-GO® TERRAIN™ 250

HIGHLY VERSATILE.



	ELECTRIC	GAS
DIMENSIONS		
Overall Length	106.5 in (271 cm)	106.5 in (271 cm)
Overall Width	48.5 in (123 cm)	48.5 in (123 cm)
Overall Height (w/o roof)	49.0 in (126 cm)	49.0 in (126 cm)
Overall Height (w/ roof)	71.6 in (182 cm)	71.6 in (182 cm)
Wheel Base	65.5 in (166 cm)	65.5 in (166 cm)
Front Wheel Track Rear Wheel Track	37.0 in (94 cm) 38.0 in (97 cm)	37.0 in (94 cm) 38.0 in (97 cm)
Ground Clearance at Differential	5.5 in (14 cm)	4.3 in (15 cm)
Cargo Box Width (inside)	44.5 in (113 cm)	44.5 in (113 cm)
Cargo Box Length (inside)	30.5 in (77 cm)	30.5 in (77 cm)
Cargo Box Depth (inside)	7.5 in (19 cm)	7.5 in (19 cm)
Cargo Box Volume	5.9 cu ft (0.17 m ³)	5.9 cu ft (0.17 m³)
POWER		
Power Source	48 Volt DC	4-Cycle 24.5 cu in (401cc) Low-Emissions
Valve Train	N/A	Single Cylinder OHV
Motor Type	Shunt Wound	N/A
Horsepower (kW)	3.0 hp (2.2 kW) Continuous	13.5 hp (9.7 kW) Exceeds SAE J1940 Std
Electrical System	48 Volt	Starter/Generator — Solid State Regulator
Batteries (qty/type)	Six, 8 Volt Deep Cycle	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal	Pedal
Air Cleaner	N/A	Replaceable Dry Cartridge
Lubrication	N/A	Pressurized Oil System
Oil Filter	N/A	Spin-On
Cooling System	N/A	Air Cooled
Fuel Capacity	N/A	5.8 Gallon (22.0 L)
Battery Charger	48V DC, 120 VAC, UL & CSA	N/A
Speed Controller	250 Amp Solid State Controller	N/A
Drivetrain	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT) Differential with Helical Gears
Transaxle	Differential with Helical Gears	
Gear Selection	Dash Mounted Forward-Neutral-Reverse	Forward-Reverse
Rear Axle Ratio	12.44:1	11.42:1 (forward), 15.78:1 (reverse)
PERFORMANCE Dry Weight (w/o betterion)	695 lb /915 kg)	810 lb (360 kg)
Dry Weight (w/o batteries)	685 lb (315 kg)	i ————————————————————————————————————
Curb Weight	1,050 lb (477 kg)	850 lb (385 kg)
Vehicle Load Capacity	800 lb (360 kg)	800 lb (360 kg)
Bed Load Capacity	500 lb (230 kg)	400 lb (180 kg)
Outside Clearance Circle	18.9 ft (5.76 m)	18.9 ft (5.76 m)
Speed (level ground)	16.9 mph \pm 0.5 mph (27.2 kph \pm 0.8 kph)	17.0 mph \pm 0.5 mph (27.4 kph \pm 0.8 kph)
Towing Capacity	500 lb (227 kg)	400 lb (180 kg)
STEERING & SUSPENSION		
Steering	Self-Compensating Rack and Pinion	Self-Compensating Rack and Pinion
Suspension	Leaf Springs with Hydraulic Shock Absorbers	Leaf Springs with Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-Adjusting Drum	Rear Wheel Mechanical Self-Adjusting Drum
Parking Brake	Self-Compensating, Single Point Engagement	Self-Compensating, Single Point Engagement
Tires	Trail Tires 20x11-10, (4 Ply Rated) Uni-Directional	Trail Tires 20x11-10, (4 Ply Rated) Uni-Directional
BODY & CHASSIS	William W. D. and W. D. and C.	William D. Oliviam D. Co.
Frame	Welded Steel with DuraShield™ Powder Coat	Welded Steel with DuraShield™ Powder Coat
Body & Finish	Injection molded TPO	Injection molded TPO
Available Body Colors	Almond, Black, British Racing Green, Burgundy, Electric Blue, Flame Red, Forest Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patriot Blue, Platinum, Steel Blue, Sunburst Orange, White, Yellow	Almond, Black, British Racing Green, Burgundy, Electric Blue, Flame Red, Forest Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patriot Blue, Platinum, Steel Blue, Sunburst Orange, White, Yellow
Standard Seat Color	Gray	Gray
Optional Seat Colors	Oyster, Tan, Black, Brown, White	Oyster, Tan, Black, Brown, White



FRONT



BACK

POPULAR OPTIONS & ACCESSORIES

- ► Fold-down windshield
- ► Roof with tubular steel struts
- ► Comfort grip steering wheel ▶ High-output LED headlights
- ▶ Taillights
- ➤ Turn signals w/ 4-way flashers
 ➤ Limited slip differential
- ▶ Weather enclosure
- ▶ Clays CarTM field kit
- ► Battery watering system with nozzle (electric only)

